Interlibrary Loan/Document Delivery
Health Sciences Library
University of North Carolina at Chapel Hill

Phone: 919-966-4998
OCLC: NOH

Ariel: 152.2.37.156

Fax: 866-242-1980
DOCLINE: NCUNCA

Warning Concerning Copyright Restrictions

The Copyright law of the United States (Title 17, United States Code) governs the making of photocopies or other reproductions of copyright material. Under certain conditions specified in the law, libraries and archives are authorized to furnish a photocopy or other reproduction. One of these specified conditions is that the photocopy or reproduction is not to be "used for any purpose other than private study, scholarship, or research". If a user makes a request for, or later uses a photocopy or reproduction for purposes in excess of "fair use", that user may be liable for copyright infringement. This institution reserves the right to refuse to accept a copying order if, in its judgement, fulfillment of the order would involve violation of copyright law.

~ Please include the information below for resends ~

Resend requests received after 3 business days may be delayed due to reshelving of materials.

OCLC or Docline ILL request # _____

Page(s) to resend: _____

UNC-CH Health Sciences Library
Interlibrary Loan

ILLiad TN: 260567

Lending String: *NOH,NRC,EKB,VPI,VPI

Patron: Khlystov, Andrei

Journal Title: Aerosol science and technology ; the journal of the American Association for Aerosol Research.

Volume: 24 Issue: 2

Month/Year: 1996

Pages: 59-68

Article Author:

Article Title: Khlystov,; A high-flow turbulent cloud chamber

Imprint: [New York, N.Y.] ; Elsevier, 1982-

ILL Number: 30405328

Call #: 4

MAY 02 2007

Location: ODYSSEY

Item #:

ARIELBorrower: NDD

Shipping Address:

Duke University
Perkins Library, ILL
Box 90183
Durham, NC 27708-0183
Fax: 919-660-5964
Ariel: 152.3.116.118

MAX COST:\$25.00IFM

CHARGE: No Charge

AST

A High-Flow Turbulent Cloud Chamber

A. Khlystov, G.P.A. Kos, and H.M. ten Brink*

BUSINESS UNIT FOSSIL FUELS, NETHERLANDS ENERGY RESEARCH FOUNDATION (ECN)
P. O. BOX 1, 1755 ZG PETTEN, THE NETHERLANDS

ABSTRACT. A large laboratory facility (cloud chamber) has been built to study cloud formation under reproducible conditions. The chamber was designed to assess the influence of anthropogenic aerosols on the microstructure of marine clouds in coastal Western Europe. For this reason the supersaturations in the chamber are low, in the order of 0.1%, typical for coastal marine stratus. The very large size (30 m^3) and flow ($30 \text{ m}^3/\text{min}$) of the chamber allow unperturbed use of conventional cloud instrumentation like Forward Scattering Spectrometer Probe (TSI Inc.) and high-flow cascade impactors for chemical analysis of aerosol and droplets. The performance of the cloud chamber was tested with laboratory-generated submicron-sized ammonium sulphate aerosol with a lognormal size distribution and varying the number concentrations. It was found that the sulphate particles above a threshold size of 0.07 or $0.1 \mu\text{m}$ in diameter (dependent on the settings) grew into droplets (became "activated"), which corresponds according to the Köhler theory to supersaturations of 0.26% and 0.15%, respectively. Estimates of the supersaturation in the chamber from the measured liquid water content (LWC) gave the same value. Tests showed that LWC, droplet spectra, and activation threshold were stable for hours and reproducible from day to day. AEROSOL SCIENCE AND TECHNOLOGY 24:59-68 (1996)

INTRODUCTION

Since industrialization man has caused large quantities of anthropogenic aerosols to form in the atmosphere. Anthropogenic aerosol particles can serve as extra cloud nuclei in addition to the natural cloud nuclei (aerosol particles). Clouds formed in polluted regions should contain more but smaller droplets (Wigley, 1989) and simple radiative transfer calculations show that this leads to an increase in reflection (albedo) of clouds. Clouds with the same liquid water content (LWC) but with extra cloud droplets do not absorb more infrared ter-

restrial radiation (Grassl, 1990). Anthropogenic aerosols thus act in an indirect way as a radiative cooling factor and therefore this effect is called the "indirect" aerosol effect.

Sensitivity ("susceptibility") studies show that the indirect effect is most important in marine stratus near polluted continents (Wigley, 1989; Charlson et al., 1992). There are two reasons for this. Marine clouds are thin and there are low numbers of natural nuclei and a small number of anthropogenic aerosol thus has maximum influence. Also it has been argued that a saturation effect occurs with respect to the numbers of cloud droplets in air with

*To whom correspondence should be addressed.

loadings of aerosol (polluted continental air). Apart from the effect on reflection of clouds, extra man-made cloud droplets inhibit the rain-out of low marine stratus clouds by drizzle. The persistence of clouds is thought to be the reason for the increased cloudiness over the last decades in coastal regions in Europe and the associated decrease in radiation (Liepert et al., 1994; Russak, 1990).

Number and size combined with composition are the governing factors for particles serving as cloud condensation nuclei (CCN) and thus the number of cloud droplets formed during cloud formation is a function of the same aerosol parameters (Pruppacher and Klett, 1978; Twomey, 1977). Consequently, both spectral and chemical composition data are vital for assessing the indirect effect. The potential cloud nuclei by size are those particles that are larger than approximately $0.04\ \mu\text{m}$ in diameter (Twomey, 1977).

The usual approach to studies of nucleation properties of aerosols involves cloud chambers. For low supersaturation ranges isothermal haze and continuous flow thermal diffusion cloud chambers are used (Alofs and Liu 1981; Hagen et al., 1990). A variation on a diffusion cloud chamber was reported as a CCN spectrometer by Hudson (1989). One of the drawbacks of these systems is the low sampling flow rate (usually less than a few liters per minute), which prevents measurements of the droplets by instrumentation that is conventionally used in cloud studies. Recently a system for CCN composition measurements was reported by Williams et al. (1994). The system consisted of a haze and a continuous-flow diffusion cloud chamber in series. The sampling rate of that system is 30 l/min and the grown droplets are sampled by virtual impactors. Here we describe an even larger cloud chamber. The very large size ($30\ \text{m}^3$) and flow ($30\ \text{m}^3/\text{min}$) of the chamber allow unperturbed use of conventional cloud instrumentation like the Forward Scattering Spectrometer Probe (TSI Inc.) for size measurements and high-flow cascade im-

pactors for chemical analysis of aerosol and droplets. Because the supersaturations in the marine clouds are low (Wigley, 1989), special care was given to establish reproducible, low supersaturations.

The very high throughput flow brings a new feature to the operation of the cloud chamber: the droplet growth occurs under turbulent conditions. Benner et al. (1989) reported a concurrent flow cloud chamber that also operated under turbulent conditions. Unfortunately, the authors could not determine the supersaturation in their chamber, which makes it difficult to make a comparison with the new chamber built here.

For calibration of the chamber, artificially generated ammonium sulphate aerosol used as reference cloud nuclei. This specific aerosol was selected according to the following criteria. The smallest and most numerous particles consist for a large part of sulphate (Twomey, 1977). In anthropogenically influenced air in Western Europe, sulphate is present as ammonium sulphate. Consequently ammonium sulphate was chosen as the reference aerosol. Also sodium sulphate was used in a limited number of tests for the following reasons. As discussed above, the most critical increase in cloud reflectivity is expected in polluted marine regions (Wigley, 1989). In coastal Western Europe a major part of the anthropogenic sulphate is present in the form of sodium sulphate (ten Brink et al., 1981). This compound has also been identified in substantial quantities in a recent related study (ten Brink, Khlystov, and Kos, unpublished data). Sodium sulphate is a result of the reaction between anthropogenic sulphuric acid and natural sea salt (NaCl) (ten Brink et al., 1981). The deliquescence point of this compound is at humidities approaching saturation (97% RH) and this fact could be a possible inhibiting factor in cloud activation. Cloud activation properties for sodium sulphate species were not found in the literature and thus have been tested here.

METHODS

Description of the Cloud Chamber

The central part of the cloud chamber facility is a 30 m³ aluminium vessel (Figure 1). Outdoor air is led into the chamber by a blower at a rate of 30 m³/min. Before entering the chamber the air passes through a humidifier. The humidifier is a 3-meter high 1.15 × 1.15 meter tower, part of which (2 m³) is filled with ceramic Raschig rings of 2.5 cm diameter. Water is poured over the column at a rate of 150 l/min from the top, against the flow of the incoming air stream. The water is heated by a controllable 50 kW electric heater. It is very important that the output of the humidifier does not depend on the outside weather conditions. The colder the outside air relative to the room air (20°C) and the lower its relative humidity, the more difficult it is to saturate the air to a temperature several degrees higher than room temperature. The humidifier proved to be able to maintain the necessary temperature difference even during days with low ambient temperatures and low relative humidity (11°C and 65%, respectively).

FIGURE 1. General view, view from the top and vertical cross-section of the ECN cloud chamber. A: filter housing; B: humidifier; C: chamber; D: tunnel.

After the humidifier, the saturated air stream enters a cylindrical vessel with a volume of approximately 30 m³. Contacting the colder walls of the vessel, the incoming air becomes supersaturated. Supersaturation is set by maintaining the water in the humidifier several degrees warmer than the room air. A higher supersaturation is achieved at a higher temperature difference. The room air temperature is measured at 4 points situated at half-height of the chamber, 10 cm from the vessel walls. The wall temperature is not directly controlled. To avoid temperature gradients in the room, two large ceiling fans stir the room air.

The air leaves the vessel through a 5-meter long 50 × 50 cm tunnel. Droplets formed in the chamber by the condensation of the supersaturated water on aerosol particles are measured in this tunnel. The very high flow rate enables the use of in-situ instruments like the Forward Scattering Spectrometer Probe (FSSP-47 and FSSP-95, Particle Measuring Systems Inc.) and high-flow cascade impactors for sampling and chemical characterization of the droplets, instruments that are also used in actual ambient cloud measurements.

It was found that the humidifier produces a very broad, irregular spectrum of droplets. The total number of these background droplets is around 50 cm⁻³. The presence of the background did not allow interpretation of experiments with a very low aerosol number because of competition for condensing water vapor with the particles. The droplet number was corrected for the presence of the background droplets. Presently the humidifier is modified to eliminate the background.

Comparison of the impactor spectra before and after passage through the (dry) chamber indicated no loss of particles with diameters less than 2 μm, but substantial loss of larger particles (presumably in the humidifier). The number of particles larger than 2 μm is negligible, however, both in the present tests with the reference aerosol and those with ambient aerosol, as com-

pared to the number of smaller particles growing into cloud droplets.

Residence Time Distribution

The mean residence time and time distribution of the air inside the chamber were found by measuring the time response to a step input of aerosol with a constant concentration. The response of the chamber to the step input is shown in Figure 2. The residence time distribution was derived from a smoothed response curve (Levenspiel, 1972) and is shown in Figure 3. The mean residence time in the chamber was found to be 61 sec, which is close to the expected residence time of 1 min. From the residence time distribution it follows that the air in the chamber is well mixed and there is no internal recirculation, dead pockets, or shunting and so on.

Model Sulphate Aerosol

Ammonium and sodium sulphate aerosols were used to check the performance of the chamber and to calibrate the chamber for the interpretation of results of ambient aerosol activation experiments. During measurements, before entering the humidi-

FIGURE 2. Time response of the aerosol concentration in the chamber to a step change in the aerosol input.

FIGURE 3. Residence time distribution of the air inside the chamber (fraction of the flow leaving the chamber per unit time).

fier the air passed through highflow absolute filters to remove the ambient aerosol. The reference aerosol was introduced after the humidifier. The aerosol was generated by spraying ammonium or sodium sulphate solution with a Wiesbadener Doppel-Inhalator or TSI 6-jet atomizer. The size distribution of the reference aerosol (Figure 4) was set to be similar to that of the

FIGURE 4. Number size distribution of the reference ammonium sulphate aerosol.

ambient aerosol and maintained constant from experiment to experiment. Activation tests were done varying the total aerosol number to check its influence on the number of resulting cloud droplets.

Aerosol / Droplet Monitoring and Sampling

The size and number concentration of the incoming aerosol were measured before the chamber with a Differential Mobility Particle Sizer (DMPS, TSI 3071) (ten Brink et al., 1983). The DMPS was set to measure particles from 0.019 to 0.6 μm in diameter. The aerosol was dried before entering the DMPS with a silica gel diffusion dryer to bring the aerosol to a dry reference state. The sheath air stream of the DMPS was also dried to avoid hygroscopic growth of aerosol inside the DMPS. Aerosol size and number concentration were also measured behind the chamber with a second DMPS system. Before entering the second DMPS the air stream passed an impactor with a 0.8 μm cutoff to remove the droplets, then was heated slightly and dried with a silica gel diffusion dryer to bring the aerosol to the dry reference state. In this way the spectrum of nonactivated particles is obtained. Comparing the spectra and absolute numbers of the aerosol before and after the chamber, the number and size of the activated particles are obtained.

It is important to bring the aerosol to the dry reference state to allow direct comparison of the aerosol size and number concentration before and after the chamber. The aerosol must be dried below the crystallization point otherwise after the chamber the aerosol will be larger than its dry size due to the hysteresis effect below the deliquescence point. The dry size also allows estimation of the supersaturation from an "activation threshold." The activation threshold can be defined as the largest dry size of a particle that has not been activated. The activation threshold is a measure of "effective" supersaturation in the chamber. The activation threshold is found from the dry aerosol spectra before and after the chamber.

The liquid water content of the droplets formed on the aerosol was measured in the tunnel with a PVM-100 probe (Gerber Scientific, Inc.). The PVM-100 probe was calibrated against filter measurements of the liquid water content. Because the cloud chamber is to be used for activation studies on actual ambient aerosol, the stability of the LWC in the system was checked with ambient aerosol; it will be shown that the performance of the chamber is not effected by variations in the spectral and chemical composition of aerosol.

The droplet spectra and the number of droplets were measured with an FSSP-47 and an FSSP-90 (Particle Measuring Systems Inc.). Cloud droplets were considered to be those particles that are larger than 2 μm , an empirical criterion selected by Leitch et al. (1986). In the next section it is demonstrated that the number of particles/droplets between the measuring ranges of DMPS and FSSP (0.6–2 μm) is small. The size calibration of the FSSP was performed with glass beads. The sensing volume of the FSSP was measured with a wire controlled by a micropositioner (Dye and Baumgardner, 1984). The droplet concentration was corrected for probe dead time and coincidence error (Baumgardner et al., 1985). The number-counting efficiency of the probe was checked by comparing the droplet number with the number of activated aerosol particles found from the aerosol sizer measurements.

An LAS (Laser Active Spectrometer, PMS), with a lower detection limit in size of 0.1 μm was used. The instrument measures the size of the wet particles and covers the size "gap" (0.6–2 μm) between the measuring ranges of DMPS and FSSP. It was found during activation tests, however, that water condensed in the monitor and the LAS could only be reliably operated for a limited period of time, typically half an hour. Measurements with the LAS gave additional information on the hygroscopic growth of particles, which are too small to serve as cloud nuclei, because they have diameters below the activation threshold,

but that accrete water to grow to sizes several times the original dry size. The measurements showed that only a small fraction of the wet particles is in the size range $0.6\text{--}2\text{ }\mu\text{m}$ (Figure 5). Consequently, FSSP and DMPS measurements give reliable information on activated and nonactivated fractions.

Cascade impactors from the University of Vienna were used for collecting the aerosol as a function of size for further analysis (Bernier, 1989). These are unique high-volume collectors with the high size resolution required for our detailed study. Special impactors were used to classify the smallest-sized aerosol. The impactors were applied to test the transmission of aerosol through the (dry) system at sizes for which the physical methods are less reliable (between 1 and $2\text{ }\mu\text{m}$).

Stabilization of the System

Because of the large geometry and the associated high heat capacity of the chamber, the system requires $1.5\text{--}2$ hours for stabilization until the heat exchange between the vessel and the room achieves its steady state. For this reason all measurements

were performed 2 hours after the start of a test to allow stabilization of the system, as will be described in more detail in the Discussion section.

RESULTS AND DISCUSSION

First, the stability of the liquid water content was tested. It was found to be stable for several hours (Figure 6), which is the best evidence for a stable performance of the chamber. The standard deviation in the LWC values during a 5-hour run was on average 7%. Figure 6 shows an "initiation" peak during the first 1.5 hours after the system was switched on. The initiation peak is caused by an initial higher temperature difference between the chamber and the incoming air stream (Figure 7). This is the reason that actual tests were performed only after this initiation time. Other evidence of the stability of the system is the fact that the droplet spectra are rather narrow (Figure 5). This is considered as a proof that the air stream in the chamber is well mixed and that the supersaturation in the chamber is quite uniform.

The major characteristic of a cloud chamber is the degree of supersaturation. It could be estimated from the activation threshold, which we defined in the previous section. The activation threshold is a measure of the "effective" supersaturation in

FIGURE 5. Droplet and particle number size distributions after the chamber as measured with FSSP and LAS.

FIGURE 6. Example of LWC measurement (the system was switched on at 12:50).

FIGURE 7. LWC and temperature difference between the incoming air stream and the walls of the chamber.

FIGURE 9. Fraction of nonactivated particles as a function of particle size.

the chamber. The activation threshold is found from the difference in the dry aerosol spectra before and after the chamber (Figure 8). The larger particles have disappeared after the chamber because they have grown into droplets (became activated), whereas the smallest particles have not. A

FIGURE 8. Comparison of dry spectra of reference ammonium sulphate aerosol before—and after—the chamber.

graph showing the fraction of nonactivated particles as a function of size is given in Figure 9. The graphs show an activation "cutoff." We took the size at half-height of the activation "cutoff" as the activation threshold.

The ultimate aim of this study was to search for the optimum conditions for activation study on marine aerosol at low supersaturations. This translated into finding a temperature setting at which the supersaturation in the chamber is on the order of 0.1%. Calibration tests with ammonium sulphate aerosol at the temperature difference set at 8° C gave an activation threshold at around 0.1 μm (Figure 9), which corresponds to a critical supersaturation of 0.15%.

Another way to assess the "effective" supersaturation is via the amount of condensed water (LWC). The condensed water was initially available for condensation in the vapor form and consequently is a measure of the amount of vapor above its saturation value. Knowing the LWC and temperature in the tunnel the water vapor content (WVC) can be deduced from which in turn we can deduce the supersaturation

in the system.

$$P = P_{sat}(T) + \frac{m}{V} \frac{RT}{M_w} = P_{sat}(T) + LWC \frac{RT}{M_w}$$

$$S_{eff} = \frac{(P - P_{sat}(T))100\%}{P_{sat}(T)} \quad (1)$$

$$= LWC \frac{RT}{P_{sat}(T)M_w} 100\%$$

in which P is the water vapor pressure, P_{sat} is the saturation vapor pressure, T is temperature, m is the mass of condensable water, V is the volume, LWC is the liquid water content, S_{eff} is the effective supersaturation, R is the gas constant, and M_w is the molecular weight of water.

The supersaturation estimated in this way was found to be $0.11 \pm 0.1\%$. This value is in fair agreement with the supersaturation found from the activation threshold, see above. A complication is the fact that droplets can only exist in equilibrium with supersaturated vapor. The equilibrium supersaturation for droplets of 5–10 μm size is on the order of 0.001%, which is an insignificant amount as compared to the calculated supersaturations. A second complication in using the latter method to assess the initial supersaturation is the fact that condensation may not have been completed during the residence time in the chamber. A variation in the number of aerosol particles indicated only little dependence of condensed water on aerosol number, however. This provides evidence that the time in the chamber is sufficient for condensation of the available water.

Activation experiments were done as a function of aerosol number maintaining the size distribution constant. The amount of activated particles versus total aerosol number concentration is given in Figure 10. The droplet number does not increase proportionally to the number of particles, which indicates the so-called saturation effect due to water depletion by growing droplets. This water-depletion effect is of less importance for studies related to the indirect aerosol effect, which are concen-

FIGURE 10. Droplet number versus total aerosol number.

trated on relatively low aerosol numbers, whereas the water depletion is more pronounced at higher aerosol numbers.

The laboratory tests are performed at higher temperatures than the temperatures in actual clouds. According to Pruppacher and Klett (1978), however, cloud activation of aerosol is almost independent of temperature. Our interest is in assessing the influence of anthropogenic aerosol on low marine clouds, which are warm wet clouds with temperatures at cloud base that are at most 10° C below surface temperature, which is small compared to differences in the physicochemical cloud-activation characteristics of the relevant salts (Pruppacher and Klett, 1978).

Because the supersaturation in the chamber arises from mixing two saturated air parcels at different temperatures—one of the “bulk” flow in the chamber and the other from the part of the flow that has contacted the colder walls; one can expect a higher supersaturation at higher (absolute) ambient (and consequently room) temperatures. Indeed, during calibration tests at outside air temperature 30° C the activation threshold for ammonium sulphate was at around 0.07 μm diameter (Figure 11), which corresponds to 0.26% supersaturation. To compensate the in-

FIGURE 11. Fraction of nonactivated particles as a function of particle size at high room temperatures and temperature difference set at 8° C.

crease in supersaturation due to a higher room temperature, the temperature difference between the humidifier and the room was reduced. At the difference of 4° C the threshold diameter was (again) at 0.1 μm , corresponding to critical supersaturation of 0.15%. For the temperature difference setting of 4° C during these high-temperature experiments the supersaturation according to the LWC was $0.12 \pm 0.02\%$. For the temperature difference of 8° C it was $0.27 \pm 0.02\%$. Both values are in rather good agreement with the supersaturations corresponding to the activation thresholds. This example shows it is possible to control the supersaturation in the chamber by varying the temperature difference setting. Unfortunately, due to the very high heat capacity of the chamber it is not possible to make "fast" supersaturation scans. Every time the temperature setting is changed the system requires 1-2 hours to stabilize again.

Na_2SO_4

Tests were performed with sodium sulphate in addition to the tests with ammonium sulphate for reasons outlined previously.

The cloud formation for similar aerosol parameters (size spectra and number concentration) did not show differences compared to those for ammonium sulphate. It was thus concluded that the higher deliquescence point of sodium sulphate as compared to ammonium sulphate is not an inhibiting factor for cloud activation of this compound. An important corollary to these experiments was that the dried sodium sulphate aerosol was in the nonhydrated form, whereas the material from which the solution for the nebulizer was prepared was the tri-hydrate form.

FSSP Calibration

Apart from the calibration of the FSSP by the standard "fiber method" a very careful test was made in which the number of cloud droplets was compared with the number of aerosol particles before and after the chamber. The difference in particle number should correspond to the number of cloud droplets formed. Low aerosol number concentrations were used in order to optimize the difference in the number of particles before and after the chamber ("particles activated"). Indeed the number of particles activated was within 10% of the number of cloud droplets formed (Figure 12). Actually this is a combined check on the performance of the cloud droplet counter (FSSP) and the particle counter(s) used. It is possibly the first absolute calibration of this kind.

CONCLUSIONS AND IMPLICATIONS

The findings of our cloud-formation studies can be summarized as follows.

1. Characterization tests showed that our high-throughput turbulent cloud chamber can maintain stable LWC, droplet spectra, and activation threshold over periods of days. This implies that the chamber is applicable as a standard system for the testing of the activation of ambient aerosol.

FIGURE 12. Comparison of droplet concentration as measured with FSSP and concentration of activated aerosol particles as derived from DMPS measurements.

2. The (stable) supersaturation in the order of 0.1%, which can be maintained for hours, is close to that found in marine stratus clouds. The supersaturation could be varied from 0.15%–0.26%.
3. The large dimensions of the chamber enable the unperturbed use and possibility of calibration of full-sized cloud instruments.

The study was financed by the National Research Program on Climate Change, project number 852066, and by the department of Economic Affairs of the Netherlands (ECN-contract number 2677). The authors are grateful to Dr. A. Berner and C. Kruisz of the University of Vienna for the measurements with their impactors.

References

- Alofs, D. J., and Liu, T.-H. (1981). *J. Atmos. Sci.* 38:2772–2778.

- Benner, W. H., Hansen, A. D. A., and Novakov, T. (1989). *Aerosol Sci. Technol.* 10:84–92.
- Berner, A. (1989). *Sci. Total Environ.* 86: 251–261.
- Baumgardner, D., Strapp, J. W., and Dye, J. E. (1985). *J. Atmos. Oceanic Technol.* 2:626–632.
- Charlson, R. J., Schwartz, S. E., Hales, J. M., et al. (1992). *Science* 43:152–163.
- Dye, J. E., and Baumgardner, D. (1984). *J. Atmos. Oceanic Technol.* 1:229–344.
- Grassl, H. (1990). In *Proceedings Symposium World Climate and Aerosols, Bunnik May 1990* (J. F. van de Vate and H.B. Tirion, eds.). ver. LUCHT, p. 5.
- Hagen, D. E., Trueblood, M. B., and Alofs, D. J. (1990). *Aerosol Sci. Technol.* 12:547–560.
- Hudson, J. G. (1989). *J. Atmos. Oceanic Technol.* 6:1055–1065.
- Leaith, R., Strapp, J. W., and Isaac, G. A. (1986). *Tellus* 38B:328–344.
- Levenspiel, O. (1972) *Chemical Reaction Engineering*. Wiley, New York.
- Liepert, B. et al. (1994). *Contr. Atm. Physics*, in press.
- Pruppacher, H. R., and Klett, J. K. (1978). *Microphysics of Clouds*. Reidel, Dordrecht, p. 141.
- Russak, V., (1990). *Tellus* 42B:206–210.
- ten Brink, H. M., Mallant, R. K. A. M., and de Vate, J. F. (1981). In *Physico-Chemical Behaviour of Atmospheric Pollutants* (B. Versino and H. Ott, eds.). Reidel, Dordrecht, p. 319.
- ten Brink, H. M., Plomp, A., Spoelstra, H., and van de Vate, J. F. (1983). *J. Aerosol Sci.* 14:589.
- Twomey, S. (1977). *Atmospheric Aerosols*. Elsevier, New York.
- Wigley, T. M. L. (1989). *Nature* 339:365.
- Williams, A. L., Alofs, D. J., Hagen, D. E., Caughey, M. E., and Schmitt, J. L. (1994). *Atmos. Chem.* 1:27–32.

Received January 20, 1995; accepted July 11, 1995.